


Gripper feeder BMZ 40-60 L



Highlights at one glance

- Easy attachment to any downstream machine, pushing or pulling \Rightarrow
- Fast pneumatic pilot release \Rightarrow
- Drive with highly dynamic linear motor \Rightarrow
- Compact CNC control for highly dynamic AC servo motors
- Design as table-top housing or space-saving built-in cassette \Rightarrow
- Compact control panel with LCD display, easy to programme
- Piece counter and auxiliary counter for generating pulses for peripheral devices
- Linking to the downstream machine with a 24V I/O unit with 18 inputs and 11 outputs \Rightarrow Options:
- Profiled clamps in various materials \Rightarrow
- Mounting plate with mechanical height adjustment \Rightarrow
- Full synchronous mode with downstream machine
- Electronic cam controller with 16 cams, eight of them with dynamics
- Fieldbus connections for PROFIBUS, PROFINET, Ether-CAT, Ethernet or VARAN \Rightarrow
- Special designs according to your specifications are possible at any time on request \Rightarrow

Technical data

Strip width
Feed length
Clamp opening
Clamping force at 6Bar
Precision
Continous tensile force
Power supply

max. 40 mm max. 60 mm max. 1 mm 480 N +/- 0.01 mm 73 N 230Vac

Stroke rate diagram without pilot release with belt weight 0.1kg

