

Gripper feeder BMZ 90-160 LD



Highlights at one glance


- Two feed grippers separately and individually programmable \Rightarrow
- Allows simultaneous advancement of parts with different lengths \Rightarrow
- \Rightarrow Endless feed possible without loss of time for gripper return
- Only one holding gripper results in very compact design \Rightarrow
- Fast pneumatic pilot release for all three grippers \Rightarrow
- Drive with two highly dynamic linear motors \Rightarrow
- Easily programmable two-axis CNC control \Rightarrow
- Can be used pushing or pulling \Rightarrow
- Easy attachment to any downstream machine \Rightarrow
- Compact 2-axis control unit with LCD display \Rightarrow
- Piece counter and auxiliary counter for generating pulses for peripheral devices \Rightarrow
- Linking to the downstream machine with a 24V I/O unit with 18 inputs and 11 outputs \Rightarrow Options:
- Proledfi gripper in various materials \Rightarrow
- Full synchronous mode with downstream machine \Rightarrow
- Electronic cam controller with 16 cams, 8 of them with dynamics \Rightarrow
- Fieldbus connections such as PROFIBUS, PROFINET, Ether-CAT, Ethernet or VARAN \Rightarrow
- Special designs according to your specifications are possible at any time on request \Rightarrow


Auriedstrasse 60


BandMotion AG www.bandmotion.ch info@bandmotion.ch CH-3178 Bösingen +41 (0)31 748 44 39


Technical data

Strip width	max. 90 mm
System-feed length	per clamp max. 80 mm
Clamp opening	max. 1 mm
Clamping force at 6 Bar	480 N
Precision	+/- 0.01 mm
Continous tensile force	91 N
Power supply	230Vac









BandMotion AG Auriedstrasse 60 CH-3178 Bösingen

www.bandmotion.ch info@bandmotion.ch +41 (0)31 748 44 39

S

40