

Gripper feeder BMZ 40-30 L



Highlights at one glance

- Can be mounted on any downstream machine or directly in the mould, push or pull useable \Rightarrow
- Fast pneumatic pilot release \Rightarrow
- Drive with highly dynamic linear motor \Rightarrow
- Compact CNC control for highly dynamic AC servo motors \Rightarrow
- Design as table-top housing or space-saving built-in cassette \Rightarrow
- Compact control panel with LCD display, easy to programme \Rightarrow
- Piece counter and auxiliary counter for generating pulses for peripheral devices \Rightarrow
- Linking to the downstream machine with a 24V I/O unit with 18 inputs and 11 outputs \Rightarrow **Options:**
- Profiled clamps in various materials \Rightarrow
- Mounting bracket with mechanical height adjustment \Rightarrow
- Full synchronous mode with downstream machine \Rightarrow
- Electronic cam controller with 16 cams, eight of them with dynamics \Rightarrow
- Fieldbus connections such as PROFIBUS, PROFINET, Ether-CAT, Ethernet or VARAN \Rightarrow
- Special designs according to your specifications are possible at any time on request \Rightarrow


Auriedstrasse 60


BandMotion AG www.bandmotion.ch info@bandmotion.ch CH-3178 Bösingen +41 (0)31 748 44 39


Technical data


Strip width	max. 40 mm
Feed length	max. 30 mm
Clamp opening	max. 1 mm
Clamping force at 6 Bar	120 N
Precision	+/- 0.01 mm
Continous tensile force	72 N
Power supply	230Vac











BandMotion AG Auriedstrasse 60 CH-3178 Bösingen www.bandmotion.ch info@bandmotion.ch +41 (0)31 748 44 39